

ALTOS® Lite Loose Tube, Gel-Filled, Single-Jacket, Single-Armoured Cable

36 fibres, single-mode (OS2)

CORNING

Corning ALTOS® Lite single-jacket, single-armoured cables are lightweight, reduced-diameter, armoured cables designed for direct-buried, duct and aerial (lashed) installation. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fibre.

Features and Benefits

Flexible, craft-friendly buffer tubes

Facilitate easy routing in closures

SZ-stranded, loose tube design

Isolates fibres from installation and environmental rigors and facilitates mid-span access

Dielectric central strength member

No preferential bend and requires no bonding or grounding


Medium-density polyethylene jacket

Rugged, durable and easy to strip while providing superior protection against UV radiation, fungus, abrasion and other environmental factors


Standards

Approvals and Listings USDA Rural Development Programs

Design And Test Criteria Telcordia GR-20, ICEA-640



Part Number: 036EUC-T4101A20



Cross Section of Order Number: 036EUC-T4101A20

Specifications

General Specifications

Environment	Outdoor
Application	Aerial, Direct Buried, Duct
Cable type	Loose Tube

ALTOS® Lite Loose Tube, Gel-Filled, Single-Jacket, Single-Armoured Cable

36 fibres, single-mode (OS2)

CORNING

General Specifications

Product type	Armoured
Fibre Category	Single-mode (OS2)

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation and assembly	-30 °C to 70 °C (-22 °F to 158 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Central Element	Dielectric
Fibre Count	36
Fibre colouring	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Turquoise
Fibres per tube	12
Number of Tube Positions	6
Number of Active Tubes	3
Buffer tube colour coding	Blue, Orange, Green
Buffer tube diameter	2.5 mm (0.1 in)
Number of filling elements	3
Tape	Water-swellaable
Number of ripcords	2
Tensile Strength Elements and/or Armouring - Layer 1	Corrugated steel tape armour
Outer jacket material	Polyethylene (PE)
Outer jacket colour	Black

Mechanical Characteristics Cable

Max. tensile strength, short-term	2700 N (600 lbf)
Max. Tensile Strength, Long-Term	890 N (200 lbf)
Weight	136 kg/km (91 lb/1000 ft)
Nominal Outer Diameter	12.1 mm (0.48 in)
Min. Bend Radius Installation	182 mm (7.1 in)
Min. Bend Radius Operation	121 mm (4.8 in)

ALTOS® Lite Loose Tube, Gel-Filled, Single-Jacket, Single-Armoured Cable

36 fibres, single-mode (OS2)

CORNING

Chemical Characteristics

RoHS

Free of hazardous substances according to RoHS 2011/65/EU

Ordering Information

Part Number	036EUC-T4101A20
Product Description	ALTOS® Lite Loose Tube, Gel-Filled Single-Jacket, Single-Armoured Cable, 36 fibres, Single-mode (OS2)
EAN Code	4056418185330



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.