

SOLO® ADSS Short-Span, Loose Tube, Gel-Filled Cable

96 F, 50 µm multimode (OM2)

CORNING

Corning SOLO® ADSS short-span cables are all-dielectric, self-supporting (ADSS) cables designed for easy and economical one-step installation in campus backbones with self-supporting installations where metallic messengers cannot be used. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fiber. The economical single-jacket design can span distances up to 600 ft in NESC light conditions, 500 ft in NESC medium conditions and 300 ft in NESC heavy conditions (see sag and tension chart for details).

This cable incorporates innovative waterblocking materials, eliminating the need for traditional flooding compound and providing efficient and craft-friendly cable preparation. While the concentric, self-supporting cable design allows easy, one-step installation using standard hardware and installation methods, the SZ-stranded, loose tube design isolates optical fibers from installation and environmental rigors and facilitates mid-span access. The ADSS optical cables are also available with a proprietary track-resistant polyethylene (TRPE) jacket suitable for installation in electric field potentials up to 25 kV.

Features and Benefits

Loose tube design

Mechanical ruggedness and environmental durability

Self-supporting

Easy, one-step installation

Track-resistant polyethylene (TRPE) jacket available

Suitable for installations up to 25 kV electric field potential

Innovative waterblocking design


Provides efficient and craft-friendly cable preparation

Standards


Approvals and Listings	RDUP 7 CFR 1755.900 (formerly RUS)
-------------------------------	---------------------------------------

Common Installations	Outdoor self-supporting aerial
-----------------------------	-----------------------------------

Design and Test Criteria	ANSI/ICEA S-87-640
---------------------------------	--------------------



Part Number: 096TN4-T4S31A20



Cross Section of Part Number: 096TN4-T4S31A20

CORNING

SOLO® ADSS Short-Span, Loose Tube, Gel-Filled Cable

96 F, 50 µm multimode (OM2)

CORNING

Specifications

General Specifications

Environment	Outdoor
Application	Self-Supporting
Cable Type	Loose Tube
Product Type	Self-Supporting
Fiber Category	50 µm MM (OM2)

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation	-30 °C to 70 °C (-22 °F to 158 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Central Element	Dielectric
Fiber Count	96
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Number of Tube Positions	8
Number of Active Tubes	8
Buffer Tube Color Coding, Layer 1	Blue, Orange, Green, Brown, Slate, White, Red, Black
Buffer Tube Diameter	2.5 mm (0.1 in)
Tape	Water-swellaable
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Number of Ripcords	2
Outer Jacket Material	Polyethylene (PE)
Outer Jacket Color	Black

Mechanical Characteristics Cable

Weight	122 kg/km (82 lb/1000 ft)
Nominal Outer Diameter	12.6 mm (0.50 in)
Min. Bend Radius Installation	189 mm (7.5 in)
Min. Bend Radius Operation	126 mm (5.0 in)

SOLO® ADSS Short-Span, Loose Tube, Gel-Filled Cable

96 F, 50 µm multimode (OM2)

CORNING

Installation Conditions

Span m (ft)	Initial Installation		NESC Light		NESC Medium		NESC Heavy	
	SAG %	Tension N (lbf)	SAG %	Tension N (lbf)	SAG %	Tension N (lbf)	SAG %	Tension N (lbf)
15 (50)	1.0	230 (52)	0.5	577 (130)	1.6	780 (175)	2.3	230 (52)
30 (100)	1.0	460 (103)	0.5	1007 (226)	1.9	1328 (299)	2.8	460 (103)
46 (150)	1.0	690 (155)	0.6	1391 (313)	2.1	1809 (407)	3.1	690 (155)
61 (150)	1.0	920 (207)	0.6	1748 (393)	2.3	2251 (506)	3.3	920 (207)
76 (250)	1.0	1150 (259)	0.6	2088 (469)	2.4	2668 (600)	3.6	1150 (259)
91 (300)	1.0	1380 (310)	0.7	2415 (543)	2.5	3067 (689)	3.7	1380 (310)
107 (350)	1.0	1610 (362)	0.7	2732 (614)	2.6	3451 (776)	-	
122 (400)	1.0	1840 (414)	0.7	3041 (684)	2.7	3823 (859)	-	
137 (450)	1.0	2070 (465)	0.7	3344 (752)	2.8	4186 (941)	-	
152 (500)	1.0	2300 (517)	0.7	3642 (819)	2.9	4541 (1021)	-	
168 (550)	1.0	2530 (569)	0.7	3935 (885)	-		-	
183 (600)	1.0	2760 (620)	0.7	4224 (950)	-		-	

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fiber Specifications

Optical Characteristics (cabled)

Fiber Core Diameter	50 µm
Fiber Category	OM2
Fiber Code	T
Performance Option Code	31
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	3.0 dB/km / 1.0 dB/km
Serial 1 Gigabit Ethernet	750 m / 500 m
Serial 10 Gigabit Ethernet	150 m / -
Min. Overfilled Launch (OFL) Bandwidth	700 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	950 MHz*km / -

Notes: 1) 50 µm multimode fiber macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel.
2) Improved attenuation and bandwidth options available.
3) Bend-insensitive single-mode fibers available on request.
4) Contact a Corning Customer Care Representative for additional information.

CORNING

SOLO® ADSS Short-Span, Loose Tube, Gel-Filled Cable

96 F, 50 µm multimode (OM2)

CORNING

Ordering Information

Part Number	096TN4-T4S31A20
Product Description	SOLO® ADSS Short-Span, Loose Tube, Gel-Filled Cable, 96 F, 50 µm multimode (OM2)
EAN Code	4056418168272



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING