

# Eclipse® Hardware Connector Housing, stubbed

1U, 24 port, 16 m (50 ft), SC duplex connectors, SC UPC, SM, ALTOS® riser cable, top right access, single cable stub

CORNING

Corning preconnectorized (“stubbed”) optical hardware is equipped with factory-terminated and -tested cable assemblies pre-installed in a variety of hardware products. “Stubbed” hardware is terminated in the factory according to the requirements of the Corning Quality Standards. This ensures connector performance and quality, therefore eliminating the time consuming and costly process of terminating cables in the field. It also reduces the number of part numbers needed for installation and minimizes the line items on an order.

## Features and Benefits

### Quality tested

Superior performance

### Factory-quality termination

Reduces time and cost

### Variety of connector and cable types

Various installation options



Part Number: EC124161259-U7001B

## Standards

**Approvals and Listings** RDUP (RUS) Listed

## Specifications

### General Specifications

|                    |                                                     |
|--------------------|-----------------------------------------------------|
| Application        | Central Office, Carrier Networks, CATV environments |
| Mounting Type      | Rack 19-in, Rack 23-in                              |
| Product Type       | Rack-Mountable Hardware                             |
| Cable Type Stubbed | ALTOS® Riser                                        |
| Fiber Category     | Single-mode (OS2)                                   |

### Design - Hardware

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| Housing Color                  | Black                                           |
| Housing Type                   | Eclipse Hardware                                |
| Cable Entry Direction          | Top-right                                       |
| Connectorization Configuration | Standard product (no dual-end connectorization) |
| Height Unit                    | 1U                                              |

CORNING

# Eclipse® Hardware Connector Housing, stubbed

1U, 24 port, 16 m (50 ft), SC duplex connectors, SC UPC, SM, ALTOS® riser cable, top right access, single cable stub

CORNING

## Design - Hardware

|                      |                  |
|----------------------|------------------|
| Connector Polish     | UPC              |
| Fiber Count          | 24               |
| Panel or Module Type | Eclipse Hardware |

## Mechanical Characteristics

|                    |                                                          |
|--------------------|----------------------------------------------------------|
| Cable Length       | 16 ft (50 m)                                             |
| Dimensions (HxWxD) | 4.4 cm x 43.9 cm x 30.2 cm (1.75 in x 17.3 in x 11.9 in) |
| Number of Cables   | 1                                                        |

## Design Adapter

|              |           |
|--------------|-----------|
| Adapter Type | SC duplex |
|--------------|-----------|

## Ordering Information

|                     |                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part Number         | EC124161259-U7001B                                                                                                                                                |
| Product Description | Eclipse® Hardware Connector Housing, stubbed 1U, 24 port, 16 m (50 ft), SC duplex connectors, SC UPC, SM, ALTOS® Riser Cable, top right access, single cable stub |
| EAN Code            | 4056418769721                                                                                                                                                     |

## Shipping Information

|                    |     |
|--------------------|-----|
| Units per Delivery | 1/1 |
| Package Contents   |     |

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

Corning Optical Communications RF LLC (Corning Gilbert) • 5310 W. Camelback Rd. • Glendale, AZ 85301 USA

800-528-5567 • FAX: 623-244-6358 • International: +1-623-245-1050 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

Page 2 | Revision date 2016-03-09

A complete listing of the trademarks of Corning Optical Communications RF is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications RF is ISO 9001

CORNING