

Eclipse® Wall-Mountable Housings

3 panel units; 36 F max.

CORNING

The Eclipse® Hardware wall-mountable connector housings provide interconnect or cross-connect capabilities between the outside plant, riser or distribution cables and the opto-electronics. The units are ideal in applications that require low-fiber-count distribution (school systems, public libraries and businesses) and are available in two sizes: the 3-panel housing and the 6-panel housing.

The Eclipse Hardware family of wall-mountable connector housings were designed with controls that maintain the fiber bend-radius throughout the unit on the segregated customer and provider sides. Locks are available on both the customer and provider doors for added security.

Additionally, the Eclipse Hardware family of wall-mountable connector housings utilize the Eclipse Hardware connector panels, which are available in 4, 6, 8, 10 and 12 termination capacities (10- and 12-fiber panels in SC connector type only). With the varied selection of panels, installers can customize the wall-mountable housing to best meet the needs of a particular application.

The wall-mountable connector housings are available empty, with adapter panels, or with pigtailed panels and splice trays for splicing within the unit.



Specifications

General Specifications

Application	Carrier Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware

Design - Hardware

Housing Type	Eclipse Hardware
Number of Panels per Housing	3
Panel or Module Type	Eclipse Hardware
Maximum number of fibers	36

Mechanical Characteristics

Dimensions (HxWxD)	33.0 cm x 30.5 cm x 10.8 cm (13.0 in x 12.0 in x 4.25 in)
--------------------	---

Eclipse® Wall-Mountable Housings

3 panel units; 36 F max.

CORNING

Ordering Information

Part Number	ECL-W3P
Product Description	Eclipse® Wall-Mountable Housing, 3 panel units, 36 F max
EAN Code	4056418193779

Shipping Information

Shipping Weight	3.2 kg (7 lb)
-----------------	---------------

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING