

# FDC® Unit

Capacity for (24) 6 inch FDC® Connector Panels or Modules and (22) 0.2 inch (Type 2R, 2S, 2M) splice trays

CORNING

Corning FDC® unit product line is a family of housings combined for the splicing and termination of fiber optic cable. Designed to support both cross-connect and inter-connect architectures, FDC units can be used in a wiring center as an interface to transmission equipment or in dedicated fiber frames where test access and reconfiguration are key requirements.

FDC units combine the benefits of connector housings and splice housings into single units. These units use standard FDC unit panels and modules and are available in 24-, 72- and 144-fiber capacities. FDC units are compact and modular, providing ample termination and splice storage capabilities.

To improve quality and reduce installation time of these FDC units, Corning recommends factory-pigtailed connector panels or modules. Both are available with a variety of connector types and come complete with factory-installed and tested connectorized pigtails. These pigtailed units are ideal for use in FDC units to speed the termination of fiber cable and provide the consistent quality performance of factory-installed and polished connectors.



## Features and Benefits

### Available with all common industry connectors

Accepts multiple connector types in a single unit

### Open design

Easier connector access

## Specifications

| General Specifications |                                                       |
|------------------------|-------------------------------------------------------|
| Application            | Central Office, Carrier Networks, Enterprise Networks |
| Mounting Type          | Rack 19-in, Rack 23-in, Wall-Mountable                |
| Product Type           | Rack-Mountable Hardware                               |

| Design - Hardware    |       |
|----------------------|-------|
| Housing Type         | FDC   |
| Housing Color        | Beige |
| Panel or Module Type | FDC   |

CORNING

# FDC® Unit

Capacity for (24) 6 inch FDC® Connector Panels or Modules and (22) 0.2 inch (Type 2R, 2S, 2M) splice trays

CORNING

## Mechanical Characteristics

|                    |                                                       |
|--------------------|-------------------------------------------------------|
| Dimensions (HxWxD) | 67.3 cm x 43.2 cm x 27.9 cm (26.5 in x 17 in x 11 in) |
|--------------------|-------------------------------------------------------|

## Ordering Information

|                     |                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------|
| Part Number         | FDC-001                                                                                                                  |
| Product Description | FDC® Unit with capacity for (24) 6 inch FDC Connector Panels or Modules and (22) 0.2 inch (Type 2R, 2S, 2M) splice trays |
| EAN Code            | 4056418193670                                                                                                            |

## Shipping Information

|                    |     |
|--------------------|-----|
| Units per Delivery | 1/1 |
|--------------------|-----|



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING