

Industrial Connector Housings (ICH)

Holds 12 CCH connector panels, black



Corning industrial connector housing (ICH) family is ideal for manufacturing and industrial applications. The ICH has a tough, baked-on black powder-coated finish, and they are IEC IP64 and NEMA 3S tested.

The housings are designed to accommodate conduit with concentric knockouts and accept standard CCH connector panels and modules. Splicing is accomplished with the splice tray holding kit that may be ordered separately. The units have a padlock outer door and a separate inner door to protect the provider side of the unit from unauthorized access. The inner door may also be locked by using an optional key lock.

The ICH (ICH-02P, ICH-06P and ICH-12P) is IEC IP64 and NEMA 3S tested with a tough, baked-on, smooth black powder-coated finish.



Part Number: ICH-12P

Features and Benefits

IP tested

Reliability in harsh environments

Routing guides, cable strain-relief provisions included

Easy, out-of-the-box installation

Keyhole mounting holes

Fast installation

Standards

RoHS

Free of hazardous substances according to RoHS 2011/65/EU

Approvals and Listings

IEC IP64 and NEMA 3s

Specifications

General Specifications	
Application	Enterprise Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware



Industrial Connector Housings (ICH)

Holds 12 CCH connector panels, black

CORNING

Design - Hardware

Housing Type	ICH
Number of Panels per Housing	12
Panel or Module Type	CCH
Splice Tray Options	Up to (12) category 2R, or (6) category 4R splice trays
Housing Color	Black

Mechanical Characteristics

Dimensions (HxWxD)	40.1 cm x 50.8 cm x 25.9 cm (16 in x 20 in x 10.2 in)
--------------------	---

Ordering Information

Part Number	ICH-12P
Product Description	Industrial Connector Housing (ICH), holds 12 CCH connector panels, black
EAN Code	4056418199566

Shipping Information

Units per Delivery	1/1
Shipping Weight	12.7 kg (28 lb)
Package Contents	Housing; installation guide; 12 blank panels; unit ID label; UCC strain-relief kit; UCC strain-relief bracket; central strength member strain-relief kit; 2 self-locking nuts, 6-32 SS; 18 1/8 x 4-in tie wraps

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING