

Wall-Mountable Building Terminal (WBT) Housing Only

with lock option, 12-fiber

CORNING

The Corning wall-mountable building terminal (WBT) is a compact interconnect and splice housing for up to 24 optical fibers. It is ideal for building entrance terminals, wiring closets, computer rooms and other controlled environments.

Twelve fibers can be accommodated using standard 6-fiber LDC modules or panels, and 24 fibers can be accommodated using 12-fiber LDC panels (SC only). Mass and single-fiber splicing with heat-shrink protection are among the supported options. The WBT unit is available with all standard Corning connector types.

Features and Benefits

Compact size (H x W x D): 6.3 x 10.6 x 2.5 in

Ideal for small locations

Separate Carrier Networks and subscriber outdoors

Minimizes disturbance of splice chamber

Lock option available on WBT

Designed for ribbon, loose tube and tight-buffered cables

Ideal for use with Corning 6- or 12-pack connector modules or panels

Top or bottom cable entry

Sealed for moisture and dust resistance

Maintains minimum bend-radius of standard fibers

Available with a factory-assembled preconnectorized cable stub

Accommodates standard Corning connector types



Part Number: WBT-012-L

Specifications

General Specifications	
Application	Customer premises environments, Carrier Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware

Wall-Mountable Building Terminal (WBT) Housing Only

with lock option, 12-fiber

CORNING

Design - Hardware

Housing Type	WBT
Number of Panels per Housing	2
Locking Availability	Lockable
Panel or Module Type	LDC
Splice Tray Options	Accommodates up to (2) category 2R splice trays

Mechanical Characteristics

Dimensions (HxWxD)	17.8 cm x 39.4 cm x 10.2 cm (7 in x 15.5 in x 4 in)
--------------------	---

Ordering Information

Part Number	WBT-012-L
Product Description	Wall-Mountable Building Terminal (WBT), with lock option, 12 F
EAN Code	4056418188997

Shipping Information

Units per Delivery	1/1
Shipping Weight	6 lb (3 kg)
Package Contents	Wall-Mountable Building Terminal (WBT), ships with 2 blank LDC panels, one UCC clamp kit, one ground bar kit, one keyed lock (with key), and cable ties

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING